



SAFETY DATA SHEET.

Issuing date 31-Mar-2015

Revision Date 31-Mar-2015

Version 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name

Recommended use of the chemical and restrictions on use

Product code 0003

Product Type Extremely flammable aerosol

Synonyms None

Supplier's details

Recommended Use Dye.
Uses advised against No information available

Manufactured For:
Auto Beauty Products Company
10835 Sanden Drive
Dallas, Texas 75238
Company Telephone: 972-680-8180

**Chemical Emergency Phone
Number** INFOTRAC 1-800-535-5053

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements

Emergency Overview

DANGER

Hazard Statements

Causes skin irritation
 Causes serious eye irritation
 Suspected of causing cancer
 Suspected of damaging fertility or the unborn child
 May cause drowsiness or dizziness
 May cause damage to organs (Central Nervous System, Central Vascular System, Eyes, Kidney, Liver, Lungs, Respiratory System, and skin) through prolonged or repeated exposure.
 May be fatal if swallowed and enters airways
 Extremely flammable aerosol
 Contains gas under pressure; may explode if heated



Appearance opaque

Physical state Aerosol

Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Wash face, hands and any exposed skin thoroughly after handling
 Wear protective gloves/protective clothing/eye protection/face protection
 Do not breathe dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Do not spray on an open flame or other ignition source
 Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention
 Specific treatment (see first aid on this label)
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice/attention
 Take off contaminated clothing and wash before reuse
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 Call a POISON CENTER or doctor/physician if you feel unwell
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None

Other information

- Toxic to aquatic life with long lasting effects

0.00803% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
ACETONE	67-64-1	30-40
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	20-30
TOLUENE	108-88-3	10-20
TITANIUM DIOXIDE	13463-67-7	1-10
N-BUTYL ALCOHOL	71-36-3	1-10
CALCIUM CARBONATE	1317-65-3	1-10
TALC	14807-96-6	1-10
2-BUTANONE	78-93-3	1-10
XYLENE	1330-20-7	1-10
ETHYL BENZENE	100-41-4	0.1-1
METHYL ISOBUTYL KETONE	108-10-1	0.1-1

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes

Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen may be necessary. If breathing has stopped, contact emergency medical services immediately.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.

Most important symptoms/effects, acute and delayed

Main Symptoms Causes skin and eye irritation. Irritating to respiratory system. May cause drowsiness or dizziness. May damage to fertility or the unborn child. May cause cancer. Harmful or fatal if swallowed and enters airways. Causes damage to organs through prolonged or repeated exposure.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Keep away from sources of ignition - No smoking. Cool containers / tanks with water spray.

Specific hazards arising from the chemical

Extremely flammable. Risk of ignition.

Explosion Data

Sensitivity to Mechanical Impact none.

Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid skin contact. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Keep can away from all sources of electricity such as electric motors and batteries. Do not spray on hot surfaces.

Environmental precautions

Environmental precautions Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Methods for cleaning up Pick up and transfer to properly labeled containers. Soak up with inert absorbent material. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Prevent product from entering drains.

7. HANDLING AND STORAGE

Precautions for safe handling**Advice on safe handling**

Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can.

Conditions for safe storage, including any incompatibilities**Technical measures/Storage conditions**

Keep away from open flames, hot surfaces and sources of ignition. Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

Incompatible products

Strong oxidizing agents, strong acids, and strong bases.

Aerosol Level

3

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ACETONE 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6: TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	74-98-6: IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ 106-97-8: TWA: 800 ppm TWA: 1900 mg/m ³ 75-28-5: TWA: 800 ppm TWA: 1900 mg/m ³
TOLUENE 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³
N-BUTYL ALCOHOL 71-36-3	TWA: 20 ppm	TWA: 100 ppm TWA: 300 mg/m ³ (vacated) S* (vacated) Ceiling: 50 ppm (vacated) Ceiling: 150 mg/m ³	IDLH: 1400 ppm Ceiling: 50 ppm Ceiling: 150 mg/m ³
CALCIUM CARBONATE 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust

TALC 14807-96-6	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	(vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	IDLH: 1000 mg/m ³ TWA: 2 mg/m ³ containing no Asbestos and <1% Quartz respirable dust
2-BUTANONE 78-93-3	STEL: 300 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 590 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 590 mg/m ³ (vacated) STEL: 300 ppm (vacated) STEL: 885 mg/m ³	IDLH: 3000 ppm TWA: 200 ppm TWA: 590 mg/m ³ STEL: 300 ppm STEL: 885 mg/m ³
XYLENE 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
METHYL ISOBUTYL KETONE 108-10-1	STEL: 75 ppm TWA: 20 ppm	TWA: 100 ppm TWA: 410 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 205 mg/m ³ (vacated) STEL: 75 ppm (vacated) STEL: 300 mg/m ³	IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m ³ STEL: 75 ppm STEL: 300 mg/m ³

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Exposure controls

Engineering Measures Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

- Eye/Face Protection** Safety glasses with side-shields.
- Skin and body protection** Chemical resistant apron. Protective gloves.
- Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state	Aerosol	Odor	Solvent
Appearance	opaque	Odor Threshold	No information available
Color	Desert Tan		

Property	Values	Remarks • Methods
-----------------	---------------	--------------------------

pH	No information available	
Melting/freezing point	No information available	
Boiling point/boiling range	No information available	
Flash Point	-97 °C / -143 °F	Based on propellant
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limits in Air		
upper flammability limit	No information available	
lower flammability limit	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Specific Gravity	0.849	
Water solubility	Practically insoluble	
Partition coefficient: n-octanol/water	No information available	
Autoignition temperature	No information available	Not applicable
Decomposition temperature	No information available	
Viscosity	No information available	
Explosive properties	No information available	

Other information

VOC Content(%) 52.93

10. STABILITY AND REACTIVITY
Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight. Keep away from children. Take precautionary measures against static discharges.

Incompatible Materials

Strong oxidizing agents, strong acids, and strong bases.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION
Information on likely routes of exposure**Product Information****Inhalation**

Vapors may irritate throat and respiratory system. May cause drowsiness and dizziness based on components. May cause irritation of respiratory tract. Avoid breathing vapors or mists.

Eye contact

Irritating to eyes. Avoid contact with eyes.

Skin contact

Irritating to skin. Repeated exposure may cause skin dryness or cracking. Prolonged skin contact may defat the skin and produce dermatitis. Avoid contact with skin.

Ingestion

Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
ACETONE 67-64-1	= 5800 mg/kg	20,000 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h
TOLUENE 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
TITANIUM DIOXIDE 13463-67-7	> 10000 mg/kg (Rat)	-	-
N-BUTYL ALCOHOL 71-36-3	= 700 mg/kg (Rat)	= 3402 mg/kg (Rabbit)	> 8000 ppm (Rat) 4 h
2-BUTANONE 78-93-3	= 2483 mg/kg (Rat)	= 5000 mg/kg (Rabbit)	= 11700 ppm (Rat) 4 h
XYLENE 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
ETHYL BENZENE 100-41-4	-	= 15400 mg/kg (Rabbit)	-
METHYL ISOBUTYL KETONE 108-10-1	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	= 8.2 mg/L (Rat) 4 h

Information on toxicological effects**Symptoms**

Symptoms of overexposure may be headache, tiredness, nausea, and vomiting. Causes respiratory irritation. Causes skin and eye irritation. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Skin corrosion/irritation**

Irritating to skin.

Eye damage/irritation

Irritating to eyes.

Sensitization

None known.

Germ Cell Mutagenicity

None known.

Carcinogenicity

The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
TOLUENE 108-88-3	-	Group 3	-	-
TITANIUM DIOXIDE 13463-67-7	-	2B	-	-
TALC 14807-96-6	-	Group 3	-	-
XYLENE 1330-20-7	-	Group 3	-	-
ETHYL BENZENE 100-41-4	A3	Group 2B	-	-
METHYL ISOBUTYL KETONE 108-10-1	A3	Group 2B	-	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicity

Product is or contains a chemical which is a known or suspected reproductive hazard.

Specific target organ systemic toxicity (single exposure)

May cause respiratory irritation. May cause drowsiness and dizziness.

Specific target organ systemic toxicity (repeated exposure)

May cause damage to organs through prolonged or repeated exposure.

Chronic toxicity

May cause adverse liver effects.

Target Organ Effects

Central nervous system, Central Vascular System (CVS), Eyes, Kidney, Liver, Lungs, Respiratory system, Skin.

Neurological effects	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.
Aspiration hazard	May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0.00803% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	22217 mg/kg
ATEmix (dermal)	12762 mg/kg
ATEmix (inhalation-gas)	871846 mg/l
ATEmix (inhalation-dust/mist)	105.9 mg/l

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
ACETONE 67-64-1	-	4.74 - 6.33 mL/L LC50 Oncorhynchus mykiss 96h 6210 - 8120 mg/L LC50 Pimephales promelas 96h static 8300 mg/L LC50 Lepomis macrochirus 96h	-	10294 - 17704 mg/L EC50 Daphnia magna 48h Static 12600 - 12700 mg/L EC50 Daphnia magna 48h
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	-	-	-	-
TOLUENE 108-88-3	433 mg/L EC50 Pseudokirchneriella subcapitata 96h 12.5 mg/L EC50 Pseudokirchneriella subcapitata 72h static	11.0 - 15.0 mg/L LC50 Lepomis macrochirus 96h static 14.1 - 17.16 mg/L LC50 Oncorhynchus mykiss 96h static 15.22 - 19.05 mg/L LC50 Pimephales promelas 96h flow-through 5.89 - 7.81 mg/L LC50 Oncorhynchus mykiss 96h flow-through 50.87 - 70.34 mg/L LC50 Poecilia reticulata 96h static 12.6 mg/L LC50 Pimephales promelas 96h static 28.2 mg/L LC50 Poecilia reticulata 96h semi-static 5.8 mg/L LC50 Oncorhynchus mykiss 96h semi-static 54 mg/L LC50 Oryzias latipes 96h static	-	5.46 - 9.83 mg/L EC50 Daphnia magna 48h Static 11.5 mg/L EC50 Daphnia magna 48h
N-BUTYL ALCOHOL 71-36-3	500 mg/L EC50 Desmodesmus subspicatus 96h 500 mg/L EC50 Desmodesmus subspicatus 72h	100000 - 500000 µg/L LC50 Lepomis macrochirus 96h static 1730 - 1910 mg/L LC50 Pimephales promelas 96h static 1740 mg/L LC50 Pimephales promelas 96h flow-through 1910000 µg/L LC50 Pimephales promelas 96h static	-	1897 - 2072 mg/L EC50 Daphnia magna 48h Static 1983 mg/L EC50 Daphnia magna 48h
TALC 14807-96-6	-	100 g/L LC50 Brachydanio rerio 96h semi-static	-	-
2-BUTANONE 78-93-3	-	3130 - 3320 mg/L LC50 Pimephales promelas 96h flow-through	-	4025 - 6440 mg/L EC50 Daphnia magna 48h Static 5091 mg/L EC50 Daphnia magna 48h 520 mg/L EC50 Daphnia magna 48h

XYLENE 1330-20-7	-	13.1 - 16.5 mg/L LC50 Lepomis macrochirus 96h flow-through 13.5 - 17.3 mg/L LC50 Oncorhynchus mykiss 96h 2.661 - 4.093 mg/L LC50 Oncorhynchus mykiss 96h static 23.53 - 29.97 mg/L LC50 Pimephales promelas 96h static 30.26 - 40.75 mg/L LC50 Poecilia reticulata 96h static 7.711 - 9.591 mg/L LC50 Lepomis macrochirus 96h static 13.4 mg/L LC50 Pimephales promelas 96h flow-through 19 mg/L LC50 Lepomis macrochirus 96h 780 mg/L LC50 Cyprinus carpio 96h semi-static 780 mg/L LC50 Cyprinus carpio 96h	-	0.6 mg/L LC50 Gammarus lacustris 48h 3.82 mg/L EC50 water flea 48h
ETHYL BENZENE 100-41-4	4.6 mg/L EC50 Pseudokirchneriella subcapitata 72h 438 mg/L EC50 Pseudokirchneriella subcapitata 96h 2.6 - 11.3 mg/L EC50 Pseudokirchneriella subcapitata 72h static 1.7 - 7.6 mg/L EC50 Pseudokirchneriella subcapitata 96h static	11.0 - 18.0 mg/L LC50 Oncorhynchus mykiss 96h static 7.55 - 11 mg/L LC50 Pimephales promelas 96h flow-through 9.1 - 15.6 mg/L LC50 Pimephales promelas 96h static 32 mg/L LC50 Lepomis macrochirus 96h static 4.2 mg/L LC50 Oncorhynchus mykiss 96h semi-static 9.6 mg/L LC50 Poecilia reticulata 96h static	-	1.8 - 2.4 mg/L EC50 Daphnia magna 48h
METHYL ISOBUTYL KETONE 108-10-1	400 mg/L EC50 Pseudokirchneriella subcapitata 96h	496 - 514 mg/L LC50 Pimephales promelas 96h flow-through	-	170 mg/L EC50 Daphnia magna 48h

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	log Pow
ACETONE 67-64-1	-0.24
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	2.8
TOLUENE 108-88-3	2.65
N-BUTYL ALCOHOL 71-36-3	0.785
2-BUTANONE 78-93-3	0.29
XYLENE 1330-20-7	3.15
ETHYL BENZENE 100-41-4	3.118
METHYL ISOBUTYL KETONE 108-10-1	1.19

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
Contaminated packaging	Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Ground	CONSUMER COMMODITY ORM-D or LIMITED QUANTITY
IATA	UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.
IMDG	UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

15. REGULATORY INFORMATION**International Inventories**

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
ACETONE	X	X	X	X	X	X	X	X
PROPANE/ISOBUTAN E/N-BUTANE	X	X	X	Not listed	X	X	X	X
TOLUENE	X	X	X	X	X	X	X	X
TITANIUM DIOXIDE	X	X	X	X	X	X	X	X
N-BUTYL ALCOHOL	X	X	X	X	X	X	X	X
CALCIUM CARBONATE	X	X	X	X	X	X	X	X
TALC	X	X	X	X	X	X	X	X
2-BUTANONE	X	X	X	X	X	X	X	X
XYLENE	X	X	X	X	X	X	X	X
ETHYL BENZENE	X	X	X	X	X	X	X	X
METHYL ISOBUTYL KETONE	X	X	X	X	X	X	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
TOLUENE - 108-88-3	108-88-3	10-20	1.0
N-BUTYL ALCOHOL - 71-36-3	71-36-3	1-10	1.0
XYLENE - 1330-20-7	1330-20-7	1-10	1.0
ETHYL BENZENE - 100-41-4	100-41-4	0.1-1	0.1
METHYL ISOBUTYL KETONE - 108-10-1	108-10-1	0.1-1	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	no

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TOLUENE 108-88-3	1000 lb	X	X	X
XYLENE 1330-20-7	100 lb			X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
ACETONE 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
TOLUENE 108-88-3	1000 lb 1 lb		RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
N-BUTYL ALCOHOL 71-36-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
2-BUTANONE 78-93-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
METHYL ISOBUTYL KETONE 108-10-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65
TOLUENE - 108-88-3	Developmental Female Reproductive
TITANIUM DIOXIDE - 13463-67-7	Carcinogen
ETHYL BENZENE - 100-41-4	Carcinogen
METHYL ISOBUTYL KETONE - 108-10-1	Carcinogen Developmental

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACETONE 67-64-1	X	X	X
TOLUENE 108-88-3	X	X	X
TITANIUM DIOXIDE 13463-67-7	X	X	X
N-BUTYL ALCOHOL 71-36-3	X	X	X
CALCIUM CARBONATE 1317-65-3	X	X	X
TALC 14807-96-6	X	X	X
2-BUTANONE 78-93-3	X	X	X
XYLENE 1330-20-7	X	X	X
ETHYL BENZENE 100-41-4	X	X	X
METHYL ISOBUTYL KETONE 108-10-1	X	X	X

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

**16. OTHER INFORMATION**

NFPA	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards -
HMIS	Health Hazard 2	Flammability 4	Physical Hazard 1	Personal protection B

Prepared By Regulatory Affairs
 Issuing date 31-Mar-2015
 Revision Date 31-Mar-2015
 Revision Note

No information available

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet