



Safety Data Sheet

Copyright, 2015, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 24-2283-0 | Version Number: | 2.03 |
| Issue Date: | 05/12/15 | Supersedes Date: | 07/02/13 |

SECTION 1: Identification

1.1. Product identifier

3M™ Perfect-It™ Machine Polish PN 06064, 06065, 06053, 39061, 06072, 6078

Product Identification Numbers

LB-K100-0410-4, 60-4550-3490-4, 60-4550-3491-2, 60-4550-3492-0, 60-4550-3639-6, 60-4550-3749-3, 60-4550-3751-9, 60-4550-5182-5, 60-4550-5183-3, 60-4550-5184-1, 60-4550-5185-8, XG-0038-1548-5

1.2. Recommended use and restrictions on use

Recommended use

Automotive

1.3. Supplier's details

| | |
|----------------------|---|
| MANUFACTURER: | 3M |
| DIVISION: | Automotive Aftermarket |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Flammable Liquid: Category 4.

Skin Sensitizer: Category 1.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark |

Pictograms



Hazard Statements

Combustible liquid.

May cause an allergic skin reaction.

Precautionary Statements

General:

Keep out of reach of children.

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wear protective gloves and eye/face protection.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

None.

7% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|--|------------|------------------------|
| Water | 7732-18-5 | 50 - 70 Trade Secret * |
| Hydrotreated Light Petroleum Distillates | 64742-47-8 | 10 - 30 Trade Secret * |
| Aluminum Oxide | 1344-28-1 | 5 - 13 Trade Secret * |
| Decamethylcyclopentasiloxane | 541-02-6 | < 7 Trade Secret * |
| Dodecamethylcyclohexasiloxane | 540-97-6 | < 5 Trade Secret * |
| Aluminum Silicate Clay | 66402-68-4 | 1 - 5 Trade Secret * |
| Ethylene oxide, polymer with ethylenediamine and propylene oxide | 26316-40-5 | < 1 Trade Secret * |
| White mineral oil (petroleum) | 8042-47-5 | < 1 Trade Secret * |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

| <u>Substance</u> | <u>Condition</u> |
|------------------|-------------------|
| Formaldehyde | During Combustion |
| Carbon monoxide | During Combustion |
| Carbon dioxide | During Combustion |

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or

bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Protect from sunlight. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|--|------------|--------|--|---|
| Aluminum, insoluble compounds | 1344-28-1 | ACGIH | TWA(respirable fraction):1 mg/m3 | A4: Not class. as human carcin |
| Aluminum Oxide | 1344-28-1 | OSHA | TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3 | |
| Aluminum Oxide | 1344-28-1 | CMRG | TWA:1 fiber/cc | |
| Decamethylcyclpentasiloxane | 541-02-6 | CMRG | TWA:10 ppm | |
| Kerosine (petroleum) | 64742-47-8 | ACGIH | TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3 | A3: Confirmed animal carcin., Skin Notation |
| Hydrotreated Light Petroleum Distillates | 64742-47-8 | CMRG | TWA:165 ppm | |
| White mineral oil (petroleum) | 8042-47-5 | CMRG | TWA:5 mg/m3;STEL:10 mg/m3 | |
| MINERAL OILS, HIGHLY-REFINED OILS | 8042-47-5 | ACGIH | TWA(inhalable fraction):5 mg/m3 | A4: Not class. as human carcin |
| Paraffin oil | 8042-47-5 | OSHA | TWA(as mist):5 mg/m3 | |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Neoprene

Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | |
|----------------------------------|--|
| General Physical Form: | Liquid |
| Specific Physical Form: | Emulsion |
| Odor, Color, Grade: | Petroleum distillate odor, grey viscous liquid |
| Odor threshold | <i>No Data Available</i> |
| pH | 7.5 - 8.5 |
| Melting point | <i>No Data Available</i> |
| Boiling Point | 375 °F |
| Flash Point | 168 °F [<i>Test Method: Closed Cup</i>] |
| Flammability (solid, gas) | Not Applicable |
| Flammable Limits(LEL) | <i>No Data Available</i> |
| Flammable Limits(UEL) | <i>No Data Available</i> |
| Vapor Pressure | <i>No Data Available</i> |
| Vapor Density | <i>No Data Available</i> |
| Density | 0.99 g/ml |
| Specific Gravity | 0.99 [<i>Ref Std: WATER=1</i>] |
| Solubility in Water | Moderate |
| Solubility- non-water | Slight |

| | |
|--|--|
| Partition coefficient: n-octanol/ water | <i>No Data Available</i> |
| Autoignition temperature | <i>No Data Available</i> |
| Decomposition temperature | <i>No Data Available</i> |
| Viscosity | 18,000 - 23,000 centipoise [<i>Test Method:</i> Tested per ASTM protocol] [<i>Details:</i> Spindle #6 @ 10rpm] |
| Hazardous Air Pollutants | 0.0007 lb HAPS/lb solids [<i>Test Method:</i> Calculated] |
| Volatile Organic Compounds | 139 g/l [<i>Test Method:</i> calculated SCAQMD rule 443.1] |
| Volatile Organic Compounds | 14.1 % weight [<i>Test Method:</i> calculated per CARB title 2] |
| VOC Less H2O & Exempt Solvents | 382 g/l [<i>Test Method:</i> calculated SCAQMD rule 443.1] |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
| None known. | |

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Dust created by cutting, grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|--------------------------------|---------|---|
| Overall product | Dermal | | No data available; calculated ATE > 5,000 mg/kg |
| Overall product | Inhalation-Dust/Mist(4 hr) | | No data available; calculated ATE > 12.5 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE > 5,000 mg/kg |
| Hydrotreated Light Petroleum Distillates | Dermal | Rabbit | LD50 > 3,160 mg/kg |
| Hydrotreated Light Petroleum Distillates | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 3.0 mg/l |
| Hydrotreated Light Petroleum Distillates | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Aluminum Oxide | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Aluminum Oxide | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 2.3 mg/l |
| Aluminum Oxide | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Decamethylcyclpentasiloxane | Dermal | Rabbit | LD50 > 15,000 mg/kg |
| Decamethylcyclpentasiloxane | Inhalation-Dust/Mist (4 hours) | Rat | LC50 8.7 mg/l |
| Decamethylcyclpentasiloxane | Ingestion | Rat | LD50 > 24,134 mg/kg |
| Dodecamethylcyclohexasiloxane | Dermal | Rat | LD50 > 2,000 mg/kg |
| Dodecamethylcyclohexasiloxane | Ingestion | Rat | LD50 > 50,000 mg/kg |
| Aluminum Silicate Clay | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Aluminum Silicate Clay | Ingestion | | LD50 estimated to be 2,000 - 5,000 mg/kg |
| White mineral oil (petroleum) | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| White mineral oil (petroleum) | Ingestion | Rat | LD50 > 5,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--|---------|---------------------------|
| Hydrotreated Light Petroleum Distillates | Rabbit | Mild irritant |
| Aluminum Oxide | Rabbit | No significant irritation |
| Dodecamethylcyclohexasiloxane | Rabbit | No significant irritation |
| Aluminum Silicate Clay | Rabbit | No significant irritation |
| White mineral oil (petroleum) | Rabbit | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|--|---------|---------------------------|
| Hydrotreated Light Petroleum Distillates | Rabbit | Mild irritant |
| Aluminum Oxide | Rabbit | No significant irritation |
| Dodecamethylcyclohexasiloxane | Rabbit | No significant irritation |
| Aluminum Silicate Clay | Rabbit | Mild irritant |
| White mineral oil (petroleum) | Rabbit | Mild irritant |

Skin Sensitization

| Name | Species | Value |
|--|------------|-----------------|
| Hydrotreated Light Petroleum Distillates | Guinea pig | Not sensitizing |
| White mineral oil (petroleum) | Guinea pig | Not sensitizing |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|--|----------|--|
| Hydrotreated Light Petroleum Distillates | In Vitro | Not mutagenic |
| Aluminum Oxide | In Vitro | Not mutagenic |
| Aluminum Silicate Clay | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| White mineral oil (petroleum) | In Vitro | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|--|------------|-------------------------|--|
| Hydrotreated Light Petroleum Distillates | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Aluminum Oxide | Inhalation | Rat | Not carcinogenic |
| Aluminum Silicate Clay | Inhalation | Multiple animal species | Some positive data exist, but the data are not sufficient for classification |
| White mineral oil (petroleum) | Dermal | Mouse | Not carcinogenic |
| White mineral oil (petroleum) | Inhalation | Multiple animal species | Not carcinogenic |

Reproductive Toxicity**Reproductive and/or Developmental Effects**

| Name | Route | Value | Species | Test Result | Exposure Duration |
|-------------------------------|-----------|----------------------------------|---------|-----------------------------|-------------------------------------|
| Dodecamethylcyclohexasiloxane | Ingestion | Not toxic to female reproduction | Rat | NOAEL 1,000 mg/kg/day | pre mating & during gestation |
| Dodecamethylcyclohexasiloxane | Ingestion | Not toxic to male reproduction | Rat | NOAEL 1,000 mg/kg/day | 28 days |
| Dodecamethylcyclohexasiloxane | Ingestion | Not toxic to development | Rat | NOAEL 1,000 mg/kg/day | pre mating & during gestation |
| White mineral oil (petroleum) | Ingestion | Not toxic to female reproduction | Rat | NOAEL 4,350 mg/kg/day | 13 weeks |
| White mineral oil (petroleum) | Ingestion | Not toxic to male reproduction | Rat | NOAEL 4,350 mg/kg/day | 13 weeks |
| White mineral oil (petroleum) | Ingestion | Not toxic to development | Rat | NOAEL 4,350 mg/kg/day | during gestation |

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|--|------------|-----------------------------------|-----------------------------------|------------------|---------------------|-------------------|
| Hydrotreated Light Petroleum Distillates | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human and animal | NOAEL Not available | |

| | | | | | | |
|--|------------|------------------------|--|--|---------------------|--|
| Hydrotreated Light Petroleum Distillates | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | | NOAEL Not available | |
|--|------------|------------------------|--|--|---------------------|--|

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|--------------------------------|------------|---|--|-------------------------|-----------------------|-----------------------|
| Aluminum Oxide | Inhalation | pneumoconiosis pulmonary fibrosis | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | occupational exposure |
| Dodecamethylcyclohexasil oxane | Ingestion | endocrine system liver respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 1,000 mg/kg/day | 28 days |
| Dodecamethylcyclohexasil oxane | Ingestion | nervous system | All data are negative | Rat | NOAEL 1,000 mg/kg/day | 28 days |
| Aluminum Silicate Clay | Inhalation | pulmonary fibrosis | Some positive data exist, but the data are not sufficient for classification | Multiple animal species | NOAEL not available | |
| Aluminum Silicate Clay | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL not available | occupational exposure |
| White mineral oil (petroleum) | Ingestion | hematopoietic system | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 1,381 mg/kg/day | 90 days |
| White mineral oil (petroleum) | Ingestion | liver immune system | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 1,336 mg/kg/day | 90 days |

Aspiration Hazard

| Name | Value |
|--|-------------------|
| Hydrotreated Light Petroleum Distillates | Aspiration hazard |
| White mineral oil (petroleum) | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

| <u>Ingredient</u> | <u>C.A.S. No</u> | <u>% by Wt</u> |
|--|------------------|----------------|
| Aluminum Oxide | 1344-28-1 | 5 - 13 |
| Aluminum Oxide (ALUMINUM OXIDE (FIBROUS FORMS ONLY)) | 1344-28-1 | 5 - 13 |

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 2 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 24-2283-0 | Version Number: | 2.03 |
| Issue Date: | 05/12/15 | Supersedes Date: | 07/02/13 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR

USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com